

Jack Richeson & Company, Inc.

Material Safety Data Sheet

Extinguishing Media: Water foam Co2 or dry powder
Special Firefighting Procedures: N/A

SECTION V- Health Hazard Data

Stability: This produce is stable
Permissible Exposure Level: None
Effects of Overexposure: None
First Aide: Ordinary measures of personal hygiene

SECTION VI- TOXICITY AND REACTIVITY DATA

Incompatibility: None
Condition to Avoid: Higher heats than 350 ft liberates
HCl

SECTION VII- TRANSPORT INFORMATION and SPILL or LEAK PROCEDURES

TDG Name: N/A
TDG Class: N/A

Steps to be taken in case material is released or spilled
-Sweep up and remove to disposal container
-Waste disposal method bury in an approved landfill

SECTION VIII- SPECIAL PROTECTION INFORMATION

Respiratory Protection: N/A
Ventilation: Use adequate ventilation
Protective Gloves: Rubber or Vinyl
Eye Protection: Safety Glasses
Other protective Equipment: None required

SECTION IX- PREPARATION INFORMATION AND SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Store in dry area
Other Precautions: None

Date: 1/12/2012

Jack Richeson & Company, Inc.

Material Safety Data Sheet

MSDS Date: January 20, 2012

SECTION I- Product Identification and Use

Product Name- Flexible PVC Sketch Trim

U.N Ident. Number: N/AP

Company Identification: Jack Richeson & Company, Inc.

557 Marcella Drive

Kimberly, Wi 54136

Emergency: 800-233-2404

Product Class: Flexible PVC Extrusions

WHMIS Class (es): Not controlled

SECTION II-Hazardous Ingredients

Hazardous Ingredients CAS Number Approx. %

SECTION III- Physical Data

Form Solid extruded shape of various colours

Odour Slight odour

PH Value N/A Freezing Point N/A

Boiling Range N/A Specific Gravity 1.52

Vapour Pressure N/A Molecular Weight N/A

Evaporation Rate N/A

Vapour Density N/A

% Volatile W/W N/A

Section IV- Fire and explosion data:

Flash Range N/A

Explosive Range (LEL-UEL) N/A